

**UNLEASH  
PRECISION  
AND POWER  
WITH KIOTI  
ZERO-TURN  
MOWERS.**





# ZXD DIESEL

The Kioti ZXD Diesel Series is set to pleasantly surprise and delight Kioti enthusiasts, blending the familiar components they adore with the added power of diesel. Equipped with a robust 1.2L Kioti diesel engine and direct drive transaxles, this machine operates seamlessly without relying on a drive belt.

Customers can select from either a 61- or 72-inch deck, both featuring a rugged frame, a shaft-driven reinforced 7-gauge fabricated

steel deck, and semi-pneumatic front casters for superior durability. Furthermore, it offers unparalleled operator comfort with a premium rubber-isolated 3-inch suspension seat and an articulating front axle, ensuring reduced fatigue and a more enjoyable mowing experience throughout the day.

Elevate your outdoor experience today with our cutting-edge zero-turn mowers.

## WARRANTY

24 months Unlimited Hours  
48 months 1500 hours Powertrain Warranty



## THE ZERO-TURN YOU HAVE BEEN WAITING FOR.





# SPECIFICATIONS

MODEL	ZXD61	ZXD72
<b>ENGINE</b>		
Type	KIOTI 1.2L 3 Cyl Diesel	KIOTI 1.2L 3 Cyl Diesel
Engine Gross hp (kW)	24.5 (18.3)	24.5 (18.3)
Displacement cu. in. (cc)	72.2 (1,233)	72.2 (1,233)
Fuel Tank Capacity gal. (l)	17.1 (65)	17.1 (65)
Fuel Requirement	Diesel	Diesel
<b>DRIVE TRAIN</b>		
Model	KIOTI Drive Motors	KIOTI Drive Motors
Displacement (Pump/Motor) cc	23cc/23cc 11cc charge pump	23cc/23cc 11cc charge pump
Clutch ft.-lb.	Independent Wet Disc	Independent Wet Disc
<b>TYRE SIZE</b>		
Front	15x6.5-8 Semi-Pneumatic	15x6.5-8 Semi-Pneumatic
Rear	26x12-16 Turf Tyre	26x12-16 Turf Tyre
<b>TRAVELING SPEEDS</b>		
Forward mph (km/h)	11 (17.7)	11 (17.7)
Reverse mph (km/h)	7.1 (11.5)	7.1 (11.5)
Parking Brake	Foot Pedal	Foot Pedal
<b>DIMENSIONS</b>		
Overall Length (mm)	2,258	2,328
Overall Width (mm)	1,515	1,515
Overall Height (mm)	2,092	2,092
Wheelbase (mm)	1,441	1,510
Width (Tyre to Tyre) (mm)	1,515	1,515
Approximate Curb Weight (kg)	875	898
<b>MOWER DECK</b>		
Mower Deck Type	Fabricated	Fabricated
Lift Mechanism	Pedal Operated Hydraulic	Pedal Operated Hydraulic
Deck Steel Thickness	7-gauge	7-gauge
Anti-Scalp Ball Rollers	6 (4 front, 2 rear)	6 (4 front, 2 rear)
Cutting Width of Mower in. (mm)	61 (1,550)	72 (1,829)
Blades	Notched	Notched
Cutting Height in. (mm)	1-5 (25-127)	1-5 (25-127)
Discharge Chute	Side (Durable Plastic)	Side (Durable Plastic)
Deck Height Adjustment	1/4" by Dial	1/4" by Dial

