



PRICE LIST

EFFECTIVE 1 MAY 2023

PAGE	MODEL		
	RESIDENTIAL		
03	MZ Rambler		
04	MZ Magnum		
05	ZT Avenger		
06	ZT Elite		
07	ZT Elite LE		
08	Maverick		
	COMMERCIAL		
09	Maverick HD		
10	Outlaw Rebel		
11	Outlaw Rogue		
12	Outlaw Renegade		





MODEL	BMZ4219BG
ENGINE	
MODEL	KOHLER KT745
DISPLACEMENT	747cc
POWER	26 HP
MAX TORQUE	57.5 Nm
FUEL CAPACITY	18.92 lts
OIL CAPACITY	1.9 lts

TRANSMISSION		
MODEL	ZT-2200 EZT	
PUMP DISPLACEMENT	10cc	
MOTOR DISPLACEMENT	10cc	
AXLE DIAMETER	25.4mm	
MOW SPEED	9.65 Kph	

MOWER DECK	
CONSTRUCTION	Fabricated - Welded
WIDTH	42 inch (1066mm)
THICKNESS	7 Gauge (4.5mm)
CUTTING HEIGHT	38mm - 114mm
HEIGHT ADJUSTMENT	Foot Assisted With Height Of Cut Dial
DISCHARGE CHUTE	Flexible rubber

FRAME	
CONSTRUCTION	Welded 50mm x 50mm steel tubing
MACHINE LENGTH	1930 mm
MACHINE WIDTH	1473 mm
WEIGHT	287 KG

WHEELS	
FRONT	11 x 4 -5 Smooth
REAR	18 x 8.5 - 8 Turf
CASTER ARMS	7.9mm

PRICING	\$7,999 INC GST
---------	------------------------





MODEL	BMZ48CX125	BMZ54KT740
ENGINE		
MODEL	Briggs & Straton CXi25	Kohler KT740
DISPLACEMENT	724 cc	725 cc
POWER	25 HP	25 HP
MAX TORQUE	54.2 Nm	56 Nm
FUEL CAPACITY	18.92 lts	18.92 lts
OIL CAPACITY	1.9 lts	1.9 lts

TRANSMISSION			
MODEL	ZT-2200 EZT	ZT-2200 EZT	
PUMP DISPLACEMENT	10cc	10cc	
MOTOR DISPLACEMENT	10cc	10cc	
AXLE DIAMETER	25.4mm	25.4mm	
MOW SPEED	9.65 Kph	9.65 Kph	

MOWER DECK		
CONSTRUCTION	Fabricated - Welded	Fabricated - Welded
WIDTH	48 inch (1220 mm)	54 inch (1372 mm)
THICKNESS	7 Gauge (4.5mm)	7 Gauge (4.5mm)
CUTTING HEIGHT	38mm - 114mm	38mm - 114mm
HEIGHT ADJUSTMENT	Foot Assisted With Height Of Cut Dial	Foot Assisted With Height Of Cut Dial
DISCHARGE CHUTE	Flexible rubber	Flexible rubber

FRAME		
CONSTRUCTION	Welded 50mm x 50mm steel tubing	Welded 50mm x 50mm steel tubing
MACHINE LENGTH	1930 mm	1930 mm
MACHINE WIDTH	1549 mm	1549 mm
WEIGHT	299 KG	312 KG

WHEELS			
FRONT	11 x 6 -5 Smooth	11 x 6 -5 Smooth	
REAR	18 X 9.5- 8 Turf	18 X 9.5- 8 Turf	
CASTER ARMS	7.9mm	7.9mm	

PRICING	\$9,250 INC GST	\$9,750 INC GST
---------	------------------------	------------------------





MODEL	BMZ48CX125	BMZ54KT740	
ENGINE			
MODEL	Kohler KT740	Kohler KT740	
DISPLACEMENT	725 cc	725 cc	
POWER	25 HP	25 HP	
MAX TORQUE	56 Nm	56 Nm	
FUEL CAPACITY	24.6 lts	18.92 lts	
OIL CAPACITY	1.9 lts	1.9 lts	

TRANSMISSION			
MODEL	ZT 2800	ZT 2800	
PUMP DISPLACEMENT	10cc	10cc	
MOTOR DISPLACEMENT	16cc	16cc	
AXLE DIAMETER	25.4mm	25.4mm	
MOW SPEED	11.26 Kph	11.26 Kph	

MOWER DECK		
CONSTRUCTION	Fabricated - Welded	Fabricated - Welded
WIDTH	54 inch (1372 mm)	60 inch (1524 mm)
THICKNESS	7 Gauge (4.5mm)	7 Gauge (4.5mm)
CUTTING HEIGHT	38mm - 114mm	38mm - 114mm
HEIGHT ADJUSTMENT	Foot Assisted With Height Of Cut Dial	Foot Assisted With Height Of Cut Dial
DISCHARGE CHUTE	Flexible rubber	Flexible rubber

FRAME		
CONSTRUCTION	Welded 50mm x 50mm steel tubing	Welded 50mm x 50mm steel tubing
MACHINE LENGTH	1892 mm	1892 mm
MACHINE WIDTH	1702 mm	1854 mm
WEIGHT	338 KG	346 KG
SEAT	High Back	High Back

WHEELS		
FRONT	12 x 6 -6 Smooth	12 x 6 -6 Smooth
REAR	20 x 12 - 10 Turf	20 x 12 - 10 Turf
CASTER ARMS	9.5 mm	9.5 mm

PRICING	\$10,699 INC GST	\$11,250 INC GST
---------	-------------------------	-------------------------



ZT ELITE



MODEL	BZS48KT740	BZS54KT745	BZS60KT745
ENGINE			
MODEL	Kohler KT740	Kohler KT745	Kohler KT745
DISPLACEMENT	725 cc	747cc	747cc
POWER	25 HP	26 HP	26 HP
MAX TORQUE	56 Nm	57.5 Nm	57.5 Nm
FUEL CAPACITY	24.6 lts	24.6 lts	24.6 lts
OIL CAPACITY	1.9 lts	1.9 lts	1.9 lts

TRANSMISSION			
MODEL	ZT 3100	ZT 3100	ZT 3100
PUMP DISPLACEMENT	10cc	10cc	10cc
MOTOR DISPLACEMENT	16cc	16cc	16cc
AXLE DIAMETER	25.4mm	25.4mm	25.4mm
MOW SPEED	11.26 Kph	11.26 Kph	11.26 Kph

MOWER DECK			
CONSTRUCTION	Fabricated - Welded	Fabricated - Welded	Fabricated - Welded
WIDTH	48 inch (1220 mm)	54 inch (1372 mm)	60 inch (1524 mm)
THICKNESS	7 Gauge (4.5mm)	7 Gauge (4.5mm)	7 Gauge (4.5mm)
CUTTING HEIGHT	38mm - 114mm	38mm - 114mm	38mm - 114mm
HEIGHT ADJUSTMENT	Foot Assisted With Height Of Cut Dial	Foot Assisted With Height Of Cut Dial	Foot Assisted With Height Of Cut Dial
DISCHARGE CHUTE	Flexible rubber	Flexible rubber	Flexible rubber

FRAME			
CONSTRUCTION	Welded 50mm x 50mm steel tubing	Welded 50mm x 50mm steel tubing	Welded 50mm x 50mm steel tubing
MACHINE LENGTH	1892 mm	1892 mm	1892 mm
MACHINE WIDTH	1549 mm	1702 mm	1854 mm
WEIGHT	368 KG	380 KG	392 KG
SUSPENSION	Independent Front Axle	Independent Front Axle	Independent Front Axle
SEAT	High Back With Armrest	High Back With Armrest	High Back With Armrest

WHEELS			
FRONT	13 x 6 -6 Smooth	13 x 6 -6 Smooth	13 x 6 -6 Smooth
REAR	22 x 10 - 10 Turf	20 x 11 - 10 Turf	20 x 11 - 10 Turf
CASTER ARMS	9.5 mm	9.5 mm	9.5 mm

PRICING	\$12,999 INC GST	\$13,695 INC GST	\$14,295 INC GST
---------	-------------------------	-------------------------	-------------------------



ZT ELITE LE

MODEL	BZS60ZT740	
ENGINE		
MODEL	Kohler ZT740 Confidant	
DISPLACEMENT	747cc	
POWER	25 HP	
MAX TORQUE	57.5 Nm	
FUEL CAPACITY	24.6 lts	
OIL CAPACITY	1.9 lts	
TRANSMISSION		
TRANSMISSION	77.0400	
MODEL	ZT 3100	
PUMP DISPLACEMENT	10cc	
MOTOR DISPLACEMENT	16cc	
AXLE DIAMETER	25.4mm	
MOW SPEED	11.26 Kph	
MOWER DECK		
CONSTRUCTION	Fabricated - Welded	
WIDTH	60 inch (1524 mm)	
THICKNESS	7 Gauge (4.5mm)	
CUTTING HEIGHT	38mm - 114mm	
HEIGHT ADJUSTMENT	Foot Assisted With Height Of Cut Dial	
DISCHARGE CHUTE	Flexible rubber	
FDAME		
FRAME CONSTRUCTION	Waldad 50 and a 50 and a facility in	
MACHINE LENGTH	Welded 50mm x 50mm steel tubing	
MACHINE WIDTH	1854 mm 392 KG	
WEIGHT		
SUSPENSION	Independent Front Axle	
SEAT	Custom High Back With Armrest	
WHEELS		
FRONT	13 x 6 -6 Smooth	
REAR	20 x 11 - 10 Turf Reaper	
CASTER ARMS	9.5 mm	

\$14,995 INC GST

PRICING



MAVERICK



MODEL	BMR54ZT740	BMR60ZT740
ENGINE		
MODEL	Kohler ZT740 Confidant	Kohler ZT740 Confidant
DISPLACEMENT	747cc	747cc
POWER	25 HP	25 HP
MAX TORQUE	57.5 Nm	57.5 Nm
FUEL CAPACITY	24.6 lts	24.6 lts
OIL CAPACITY	1.9 lts	1.9 lts

TRANSMISSION			
MODEL	ZT 3200	ZT 3200	
PUMP DISPLACEMENT	10cc	10cc	
MOTOR DISPLACEMENT	16cc	16cc	
AXLE DIAMETER	28.56mm	28.56mm	
MOW SPEED	14.48 Kph	14.48 Kph	

MOWER DECK		
CONSTRUCTION	Fabricated - Welded	Fabricated - Welded
WIDTH	54 inch (1372 mm)	60 inch (1524 mm)
THICKNESS	7 Gauge (4.5mm)	7 Gauge (4.5mm)
CUTTING HEIGHT	38mm - 114mm	38mm - 114mm
HEIGHT ADJUSTMENT	Foot Assisted With Height Of Cut Dial	Foot Assisted With Height Of Cut Dial
DISCHARGE CHUTE	Flexible rubber	Flexible rubber

FRAME		
CONSTRUCTION	Welded 50mm x 50mm steel tubing	Welded 50mm x 50mm steel tubing
MACHINE LENGTH	2032 mm	2032 mm
MACHINE WIDTH	1702 mm	1854 mm
WEIGHT	456 KG	468 KG
SUSPENSION	Independent Front Axle - Rear Frame	Independent Front Axle - Rear Frame
SEAT	High Back With Armrest	High Back With Armrest
ROPS	STD	STD

WHEELS		
FRONT	13 x 6.5 -6 Smooth	13 x 6.5 -6 Smooth
REAR	23 x 11 - 12 Turf Reaper	23 x 11 - 12 Turf Reaper
CASTER ARMS	12.7 mm	12.7 mm

PRICING	\$16,500 INC GST	\$16,998 INC GST
---------	-------------------------	-------------------------



MAVERICK HD

MODEL	BMH48CV749	BMH54CV749	BMH60CV749
ENGINE			
MODEL	Kohler ECV749 EFI	Kohler ECV749 EFI	Kohler ECV749 EFI
DISPLACEMENT	747 cc	747 cc	747 cc
POWER	25.5 HP	25.5 HP	25.5 HP
MAX TORQUE	55.5 Nm	55.5 Nm	55.5 Nm
FUEL CAPACITY	24.6 lts	24.6 lts	24.6 lts
OIL CAPACITY	1.9 lts	1.9 lts	1.9 lts

TRANSMISSION			
MODEL	ZT 3400	ZT 3400	ZT 3400
PUMP DISPLACEMENT	12cc	12cc	12cc
MOTOR DISPLACEMENT	16cc	16cc	16cc
AXLE DIAMETER	28.56mm	28.56mm	28.56mm
MOW SPEED	14.48 Kph	14.48 Kph	14.48 Kph

MOWER DECK			
CONSTRUCTION	Fabricated - Welded	Fabricated - Welded	Fabricated - Welded
CUTTING WIDTH	48 inch (1220 mm)	54 inch (1372 mm)	60 inch (1524 mm)
THICKNESS	7 Gauge (4.5mm)	7 Gauge (4.5mm)	7 Gauge (4.5mm)
CUTTING HEIGHT	38mm - 114mm	38mm - 114mm	38mm - 114mm
HEIGHT ADJUSTMENT	Foot Assisted With Height Of Cut Dial	Foot Assisted With Height Of Cut Dial	Foot Assisted With Height Of Cut Dial
DISCHARGE CHUTE	Flexible rubber	Flexible rubber	Flexible rubber

FRAME			
CONSTRUCTION	Welded 50mm x 50mm steel tubing	Welded 50mm x 50mm steel tubing	Welded 50mm x 50mm steel tubing
MACHINE LENGTH	2032 mm	2032 mm	2032 mm
MACHINE WIDTH	1549 mm	1702 mm	1854 mm
WEIGHT	464 KG	475 KG	486 KG
SUSPENSION	Independent Front Axle - Rear Frame	Independent Front Axle - Rear Frame	Independent Front Axle - Rear Frame
SEAT	Mechanical Suspension High Back With Armrest	Mechanical Suspension High Back With Armrest	Mechanical Suspension High Back With Armrest
ROPS	STD	STD	STD

WHEELS			
FRONT	13 x 6.5-6 Smooth	13 x 6.5-6 Smooth	13 x 6.5-6 Smooth
REAR	23 x 9 -12 Turf Reaper	23 x 11 -12 Turf Reaper	23 x 11 -12 Turf Reaper
CASTER ARMS	12.7 mm	12.7 mm	12.7 mm

PRICING	\$18,494 INC GST	\$18,995 INC GST	\$19,494 INC GST
---------	-------------------------	-------------------------	-------------------------





MODEL	BRB61EVO781	BRB72EVO820
ENGINE		
MODEL	Kawasaki EVO781 EFI	Kohler ECV820 EFI
DISPLACEMENT	780 cc	822 cc
POWER	31 HP	35 HP
MAX TORQUE	64.9 Nm	64.8 Nm
FUEL CAPACITY	49.2 lts	49.2 lts
OIL CAPACITY	2.1 lts	2.1 lts

TRANSMISSION		
MODEL	ZT 4400	ZT 4400
PUMP DISPLACEMENT	12cc	12cc
MOTOR DISPLACEMENT	16cc	16cc
AXLE DIAMETER	35 mm	35 mm
MOW SPEED	19.31 Kph	19.31 Kph

MOWER DECK		
CONSTRUCTION	Fabricated - Welded - Sloped	Fabricated - Welded - Sloped
WIDTH	61 inch (1549 mm)	72 inch 1828 mm)
THICKNESS	3 Gauge (6 mm)	3 Gauge (6 mm)
CUTTING HEIGHT	25mm - 127mm	25mm - 127mm
HEIGHT ADJUSTMENT	Foot Assisted With Height Of Cut Dial	Foot Assisted With Height Of Cut Dial
DISCHARGE CHUTE	Flexible rubber	Flexible rubber

FRAME		
CONSTRUCTION	Welded 38mm x 76mm steel tubing	Welded 38mm x 76mm steel tubing
MACHINE LENGTH	2336 mm	2336 mm
MACHINE WIDTH	1917 mm	2197 mm
WEIGHT	627 KG	643 KG
SUSPENSION	-	-
SEAT	Mechanical Suspension High Back With Armrest	Mechanical Suspension High Back With Armrest
ROPS	STD	STD

WHEELS		
FRONT	13 x 6.5-6 Smooth	13 x 6.5-6 Smooth
REAR	24 x 12 -12 Turf Reaper	24 x 12 -12 Turf Reaper
CASTER ARMS	12.7 mm	12.7 mm

 PRICING
 \$23,045 INC GST
 \$23,894 INC GST





MODEL	BRG61385KA	BRG61385KA
ENGINE		
MODEL	Kawasaki FX1000 EFI	Kawasaki FX1000 EFI
DISPLACEMENT	999 cc	999 cc
POWER	38.5 HP	38.5 HP
MAX TORQUE	78.4 Nm	78.4 Nm
FUEL CAPACITY	49.2 lts	49.2 lts
OIL CAPACITY	2.1 lts	2.1 lts

TRANSMISSION		
MODEL	Hydro-Gear Pumps - Parker Wheel Motors	Hydro-Gear Pumps - Parker Wheel Motors
PUMP DISPLACEMENT	16cc	16cc
MOTOR DISPLACEMENT	18ci	18ci
AXLE DIAMETER	31.75 mm	31.75 mm
MOW SPEED	20.92 Kph	20.92 Kph

MOWER DECK		
CONSTRUCTION	Fabricated - Welded - Sloped	Fabricated - Welded - Sloped
WIDTH	61 inch (1549 mm)	72 inch 1828 mm)
THICKNESS	3 Gauge (6 mm)	3 Gauge (6 mm)
CUTTING HEIGHT	50mm - 127mm	50mm - 127mm
HEIGHT ADJUSTMENT	Foot Assisted With Height Of Cut Dial	Foot Assisted With Height Of Cut Dial
DISCHARGE CHUTE	Flexible rubber	Flexible rubber

FRAME		
CONSTRUCTION	Welded 38mm x 76mm steel tubing	Welded 38mm x 76mm steel tubing
MACHINE LENGTH	2336 mm	2336 mm
MACHINE WIDTH	1917 mm	2197 mm
WEIGHT	697 KG	723 KG
SUSPENSION	Independent Front Axle - 3 Link Rear Axle Trailing Arm	Independent Front Axle - 3 Link Rear Axle Trailing Arm
SEAT	Mechanical Suspension High Back With Armrest	Mechanical Suspension High Back With Armrest
ROPS	STD	STD

WHEELS		
FRONT	13 x 6.5-6 Smooth	13 x 6.5-6 Smooth
REAR	24 x 12 -12 Turf Reaper	24 x 12 -12 Turf Reaper
CASTER ARMS	12.7 mm	12.7 mm

PRICING \$27,775 INC GST \$28,380 INC GST



OUTLAW RENEGADE



MODEL	BRN61247PM
ENGINE	
MODEL	Perkins Diesel
DISPLACEMENT	1100 cc
POWER	24.7 HP
MAX TORQUE	86 Nm
FUEL CAPACITY	49.2 lts
OIL CAPACITY	ТВА

TRANSMISSION	
MODEL	Hydro-Gear Pumps - Parker Wheel Motors
PUMP DISPLACEMENT	16cc
MOTOR DISPLACEMENT	18ci
AXLE DIAMETER	31.75 mm
MOW SPEED	20.92 Kph

MOWER DECK	
CONSTRUCTION	Fabricated - Welded - Sloped
WIDTH	61 inch (1549 mm)
THICKNESS	3 Gauge (6 mm)
CUTTING HEIGHT	50mm - 127mm
HEIGHT ADJUSTMENT	Foot Assisted With Height Of Cut Dial
DISCHARGE CHUTE	Flexible rubber

FRAME	
CONSTRUCTION	Welded 38mm x 76mm steel tubing
MACHINE LENGTH	2311 mm
MACHINE WIDTH	1917 mm
WEIGHT	844 KG
SUSPENSION	Independent Front Axle - 3 Link Rear Axle Trailing Arm
SEAT	Mechanical Suspension High Back With Armrest
ROPS	STD

WHEELS	
FRONT	13 x 6.5-6 Smooth
REAR	26 x 12 -12 Turf Reaper
CASTER ARMS	12.7 mm

PRICING	\$36,800 INC GST
---------	-------------------------

